

Delock Power Socket with childproof lock and USB PD charger 20 W

Description

This power socket by Delock provides one **USB Type-C™** and **two USB Type-A** charging ports. The USB charging ports supports common fast charging protocols. Connected devices can be charged with **up to 20 W**.



Item no. 11498

EAN: 4043619114986

Country of origin: China

Package: Retail Box

Technical details

- Connectors:
 - Input:
 - 1 x plug CEE 7/7
 - Output:
 - 1 x power socket CEE 7/3 with childproof lock
 - 1 x USB Type-C™ female
 - 2 x USB Type-A female
- Rated current socket CEE 7/3: 16.0 A / 250 V~
- Rated power socket CEE 7/3: 4000.0 W
- USB Charger:
 - Input: AC 250 V / 50 Hz / 0.5 A
 - Output power: max. 20.0 W total
 - USB-A: 5.0 V / 3.0 A, 9.0 V / 2.22 A, 12.0 V / 1.67 A
 - USB-C™: 5.0 V / 3.0 A, 9.0 V / 2.22 A, 12.0 V / 1.67 A
 - Over current protection, over heating protection, short circuit protection
- Average active efficiency 85.63 %
- Efficiency at low load (10 %) 74.98 %
- No-load power consumption 0.09 W
- Colour: white
- Dimensions (LxWxH): ca. 80 x 70 x 55 mm

Package content

- Power socket
- User manual

Images



General

Specification:	USB Power Delivery 2.0
Protection:	Input overvoltage protection Short circuit protection Overheating protection

Interface

Connector:	1 x plug CEE 7/7
Connector 1:	1 x power socket CEE 7/3 with childproof lock
Connector 2:	1 x USB Type-C™ female 2 x USB Type-A female

Physical characteristics

Length:	80 mm
Width:	70 mm
Height:	55 mm
Colour:	white

Power supply

Power supply input:	AC 100 - 240 V / 50 - 60 Hz / 0.5 A
Power supply output:	5.0 V / 3.0 A 12,0 V / 1,67 A 9.0 V / 2.22 A

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@delock.de
Website	www.delock.de