



Delock External Enclosure for 3.5" SATA HDD with USB Type-CTM female transparent - tool free

Description

This plastic enclosure by Delock can be used for the installation of a **3.5" SATA hard drive**. The included USB cables allow the connection to a free USB Type-A or USB-CTM port.

Transparent enclosure with stand

The **sturdy, transparent plastic housing** provides a view inside to quickly see which memory is inside. A stand is supplied for vertical operation.

HDD installation without tools

The special feature of this enclosure is that **no tools** are required to install the HDD. The lid can be pushed backwards by a little pressure, the HDD will be attached to the SATA port and then the lid is reattached until it locks.



Specification

- Connectors:
 - external:
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-CTM female
 - 1 x DC jack
 - internal:
 - 1 x SATA 6 Gb/s 22 pin receptacle
- On / Off switch
- Suitable for 3.5" SATA HDD:
 - SATA HDD up to 6 Gb/s
 - HDD up to 10 TB
- Chipset: VIA VL716
- Data transfer rate:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- LED indicator for power and access
- Transparent plastic housing
- Dimensions (LxWxH): ca. 179 x 116 x 30 mm
- Hot Swap, Plug & Play

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.0 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 10 mm

System requirements

- Chrome OS 75.0 or above
- Linux Kernel 3.3 or above
- Mac OS 10.14.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-CTM port or
- PC or laptop with a free USB Type-A port

Package content

Item no. 42623

EAN: 4043619426232

Country of origin: China

Package: Retail Box





- 3.5" external enclosure
- Cable USB-C™ male to USB-C™ male, length ca. 50 cm
- Cable USB-C™ male to USB Type-A male, length ca. 1 m
- Stand
- Power supply
- User manual

Images





General	
Function:	Hot Swap
	Plug & Play
Suitable for data medium:	2.5"
	3.5"
	SSD or HDD
Supported operating system:	Windows 7 32-bit
	Windows 7 64-bit
	Windows 8.1 32-bit
	Windows 8.1 64-bit
	Windows 10 32-bit
	Windows 10 64-bit
	Linux Kernel 3.3 or above
	Chrome OS 75.0 or above
	Mac OS 10.14.6 or above
Interface	
External:	1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female
	1 x DC jack
Internal:	1 x SATA 6 Gb/s 22 pin receptacle
Technical characteristics	
Chipset:	VIA VL716
Physical characteristics	
Housing material:	Plastic
Length:	179 mm
Width:	116 mm
Height:	30 mm
Colour:	transparent