



LevelOne 1.25Gbps Single-mode SFP Transceiver, 80km, 1550nm

Brand : LevelOne

Product code: SFP-3611

Product name : 1.25Gbps Single-mode SFP Transceiver, 80km, 1550nm



1.25 Gbps, SFP, LC, 1550 nm, 80 km

[LevelOne 1.25Gbps Single-mode SFP Transceiver, 80km, 1550nm:](#)

LevelOne SFP-3611 is a high performance and costeffective single-mode SFP transceiver. Intended for use with Gigabit Ethernet, it provides up to 1.25 Gbps bi-directional data transfer rate on a single duplex fiber core. For use with 9 micron fiber cables, it can reach a distance of up to 80km. The SFP-3611 transceiver operates using a wavelength of 1550nm with a DFB Laser Diode light source and has a LC connector.



- 1550nm DFBLD
- Data Rate: 1.25Gbps,NRZ
- Single +3.3V Power Supply
- RoHS Compliant and Lead-free
- AC/AC Differential Electrical Interface
- Compliant with Multi-Source Agreement(MSA)
- Duplex LC Connector
- Compliance with specifications for IEEE-802.3z Gigabit Ethernet at 1.25Gbps
- Compliance with ANSI specifications for Fibre Channel applications at 1.06bps
- No configuration or installation software required
- Eye Safety Designed to meet LASER Class 1 comply with EN60825-1

Performance		Certificates	
SFP transceiver type *	Fiber optic	Compliance certificates	RoHS
Maximum data transfer rate *	1250 Mbit/s	Safety	EN 60825-1
Interface type *	SFP	Certification	CE, FCC
Single-mode fiber (SMF) supported	✓	Operational conditions	
Fiber optic connector	LC	Operating temperature (T-T)	0 - 70 °C
Fiber cable diameters supported (core/cladding)	9/125 µm	Storage temperature (T-T)	-40 - 85 °C
Maximum transfer distance	80000 m	Operating relative humidity (H-H)	5 - 95%
Wavelength	1550 nm	Weight & dimensions	
Tx power (min)	0 dBmW	Width	57 mm
Tx power (max)	5 dBmW	Depth	12 mm
Link budget	23 dB	Height	13.7 mm
Networking standards	IEEE 802.3z	Weight	20 g
Duplex system	Full	Packaging content	
Fiber ports quantity	1	Quantity per pack	1 pc(s)
Features		Packaging data	
Plug and Play	✓	Package width	106 mm
Hot-swap	✓	Package depth	20 mm
Power		Package height	65 mm
Input voltage	3.3 V	Package weight	35 g
Maximum voltage	6 V	Logistics data	
Maximum current	300 A	Harmonized System (HS) code	85369010



4015867155172



4015867240304

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.