Dahua Technology ASI6213J-MW access control reader Face recognition terminal Black, Grey

Brand : Dahua Technology

Product code: ASI6213J-MW

Product name : ASI6213J-MW

- 4.3-inch LCD touch screen; resolution 480 × 272
- 2MP wide-angle dual lens camera; support DWDR, white light fill light and IR fill light
- Support face, card, password unlock and unlock through their combinations; support unlock by period
- User data can be stored at the access controller; can hold 6000 face images and work without network
- Face-camera distance: 0.3 m-1.5 m
- Face verification accuracy 99.5%; face comparison speed 0.3s per person; low false recognition rate; support liveness detection

4.3" TFT (480 × 272), 2MP CMOS, Card/Password/Face unlock, Wiegand, Ethernet, USB2.0, RS-485
Dahua Technology ASI6213J-MW. Display diagonal: 10.9 cm (4.3"), Screen shape: Flat, Touchscreen technology: Capacitive. Sensor type: CMOS, Total megapixels: 2 MP. Supported network protocols: IPv4; RTSP; RTP; TCP; UDP; P2P. Input voltage: 12 V, Input current: 2 A, Power consumption (typical): 24 W. Width: 87.5 mm, Depth: 22.5 mm, Height: 174 mm

Technical details	
Type *	Face recognition terminal
Wiegand interface	✔
Anti-passback	✔
Face capacity	6000
Face recognition distance	0.3 - 1.5 m
Face recognition duration	0.3 s
Face recognition accuracy	99.5%
User capacity	6000 user(s)
Temperature alarm	✔
Password capacity	6000
Record capacity	150000
Interoperability	CGI
Open Supervised Device Protocol (OSDP)	✔
Software development kit (SDK) support	✔
Voice prompts	✔
Exit button	✔
Lock control	✔
Duress alarm	✔
Active tampering alarm	✔
Holiday period	128 h
Product colour	Black, Grey
International Protection (IP) code	IP65
Certification	CE FCC
Display	
Display diagonal	10.9 cm (4.3")

Display	
Screen shape	Flat
Touchscreen	✔
Touchscreen technology	Capacitive
Camera	
Sensor type	CMOS
Total megapixels	2 MP
Wide Dynamic Range (WDR)	✔
Infrared (IR) light	✔
Performance	
Built-in processor	✔
Ports & interfaces	
Ethernet LAN (RJ-45) ports	1
Supported network protocols	IPv4; RTSP; RTP; TCP; UDP; P2P
RS-485 ports	1
USB port	✔
Alarm input/output	✔
Power	
Input voltage	12 V
Input current	2 A
Power consumption (typical)	24 W
Weight & dimensions	
Width	87.5 mm
Depth	22.5 mm
Height	174 mm
Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Operating relative humidity (H-H)	5 - 95%

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 14-NOV-2026. Prints or copies of Information are only valid on the printed Publication date